

CASE NO.: 50P4581
Serial No.: 09/833,490
August 16, 2004
Page 2

PATENT
Filed: April 12, 2001

1. (currently amended) A communication interface device, comprising:
at least one wireless Internet packet (IP) transceiver;
at least one flash memory card electrically connected to the transceiver and configured for engaging a flash memory slot of a computing device; and
at least one universal serial bus (USB) connector electrically connected to the transceiver, wherein the transceiver and flash memory card are integral with each other to establish a housing separate from the computing device with which the flash memory card can be engaged.
2. (original) The device of Claim 1, wherein the wireless transceiver operates in a frequency range of between two thousand three hundred million Hertz and two thousand three hundred ten million Hertz (2300mHz-2310mHz), inclusive.
3. (canceled).
4. (currently amended) The device of Claim [3]1, wherein the USB connector is connected to the transceiver with a cord.
5. (original) The device of Claim 4, wherein the USB connector is a first USB connector, and the device includes a second USB connector attached to the cord and detachably engageable with the housing.
6. (currently amended) The device of Claim [3]1, further comprising at least one light emitting diode (LED) mounted on the housing and operable at least to indicate whether the transceiver is communicating with a base station.
7. (currently amended) ~~The device of Claim 1~~ A communication interface device, comprising:
at least one wireless Internet packet (IP) transceiver;
at least one flash memory card electrically connected to the transceiver; and

1168-19.AMD

CASE NO.: 50P4581
Serial No.: 09/833,490
August 16, 2004
Page 3

PATENT
Filed: April 12, 2001

at least one universal serial bus (USB) connector electrically connected to the transceiver.

wherein the memory card has one and only one chamfered surface.

8. (original) The device of Claim 7, wherein the memory card has a length of fifty millimeters (50mm) and a width of twenty one and a half millimeters (21.5mm).

9. (original) The device of Claim 8, wherein the flash memory card has ten and only ten connectors.

10. (original) The device of Claim 9, wherein the memory card has a thickness of about two and eight-tenths millimeters (2.8mm).

11. (currently amended) The device of Claim [3]1, further comprising at least one antenna supported on the housing and electrically connected to the transceiver.

12. (original) The device of Claim 11, wherein the antenna is directional.

13. (currently amended) A wireless communication device for providing at least two communication interfaces, comprising:

at least one antenna;

at least a first computer communication interface component electrically associated with the antenna, the first computer communication interface component defining a first interface format and being a memory device; and

at least a second computer communication interface component electrically associated with the antenna, the second computer communication interface component defining a second interface format, wherein the device can be removably attached to a user terminal separate from the device

1168-19.AMD

CASE NO.: 50P4581
Serial No.: 09/833,490
August 16, 2004
Page 4

PATENT
Filed: April 12, 2001

used to establish wireless communication between ~~at least one~~ the user terminal and at least one base station using one of the interface formats.

14. (original) The device of Claim 13, wherein the first interface format is a flash memory format and the second interface format is selected from the group of formats comprising: universal serial bus (USB) format, Bluetooth wireless format, and ILink format.

15. (original) The device of Claim 13, wherein the first interface format is a flash memory format and the second interface format is a universal serial bus (USB) format.

16. (original) The device of Claim 13, further comprising a wireless IP transceiver electrically connected to the antenna.

17. (original) The device of Claim 16, wherein the wireless transceiver operates in a frequency range of between two thousand three hundred million Hertz and two thousand three hundred ten million Hertz (2300mHz-2310mHz), inclusive.

18. (original) The device of Claim 16, wherein the second computer communication interface component includes at least one USB connector, and the USB connector is connected to the transceiver with a cord.

19. (original) The device of Claim 18, wherein the USB connector is a first USB connector, and the device includes a second USB connector attached to the cord and detachably engageable with a housing supporting the transceiver.

20. (original) The device of Claim 19, further comprising at least one light emitting diode (LED) mounted on the housing and operable at least to indicate whether the transceiver is communicating with a base station.

1168-19.AMD

CASE NO.: 50P4581
Serial No.: 09/833,490
August 16, 2004
Page 5

PATENT
Filed: April 12, 2001

21. (original) The device of Claim 20, further comprising at least one audio speaker on the housing.

22. (original) The device of Claim 20, further comprising at least one battery included in the housing.

23. (original) The device of Claim 22, further comprising at least one audio or visual indication of a low voltage condition of the battery.

24. (original) The device of Claim 22, further comprising at least one charger port on the housing and electrically connected to the battery.

25. (original) The device of Claim 13, wherein the antenna is directional.

26. (currently amended) A device for effecting wireless communication between a user terminal and at least one base station, comprising:

wireless transmitting means;

first communication interface and flash memory means engageable with a user terminal for communicating IP data from the user terminal to the base station using the wireless transmitting means; and

~~second communication interface means attached to the first communication interface and flash memory means and engageable with a user terminal for communicating IP data from the user terminal to the base station using the wireless transmitting means, the first and second communication interface means being contained on a housing separate from the user terminal.~~

27. (original) The device of Claim 26, wherein the first communication interface and flash memory means is at least one flash memory card, the second communication interface means is at least one

1108-19.AMTD

CASE NO.: 50P4581
Serial No.: 09/833,490
August 16, 2004
Page 6

PATENT
Filed: April 12, 2001

universal serial bus (USB) connector, and the wireless transmitting means is at least one wireless Internet packet (IP) transceiver.

28. (original) The device of Claim 27, wherein the wireless transceiver operates in a frequency range of between two thousand three hundred million Hertz and two thousand three hundred ten million Hertz (2300mHz-2310mHz), inclusive.

29. (currently amended) The device of Claim 27, wherein the transceiver and flash memory card are housed integrally together to establish ~~the~~ housing.

30. (original) The device of Claim 29, wherein the USB connector is connected to the transceiver with a cord.

31. (original) The device of Claim 30, wherein the USB connector is a first USB connector, and the device includes a second USB connector attached to the cord and detachably engageable with the housing.

32. (original) The device of Claim 31, further comprising at least one light emitting diode (LED) mounted on the housing and operable at least to indicate whether the transceiver is communicating with a base station.

33. (original) The device of Claim 32, further comprising at least one audio speaker on the housing.

34. (original) The device of Claim 29, further comprising at least one battery included in the housing.

35. (original) The device of Claim 34, further comprising at least one audio or visual indication of a low voltage condition of the battery.

1168-19.AMD

CASE NO.: 50P4581
Serial No.: 09/833,490
August 16, 2004
Page 7

PATENT
Filed: April 12, 2001

36. (original) The device of Claim 34, further comprising at least one charger port on the housing and electrically connected to the battery.

37. (original) The device of Claim 29, further comprising at least one antenna supported on the housing and electrically connected to the transceiver.

38. (original) The device of Claim 37, wherein the antenna is directional.

39. (original) The device of Claim 1, further comprising a base station communicating with the device.

40. (original) The device of Claim 13, further comprising a base station communicating with the device.

41. (original) The device of Claim 26, further comprising a base station communicating with the device.

42. (original) A logic device usable by a user terminal for executing method acts comprising:
determining whether at least a first or second computer communication interface component is engaged with the terminal; and

if a computer communication interface component is engaged with the terminal:

determining whether the first computer communication interface component is engaged with the terminal, and if so, invoking a memory device driver module associated with the first computer communication interface component, and otherwise invoking a device driver module associated with the second computer communication interface component.

1168-19.AMD

CASE NO.: 50P4581
Serial No.: 09/833,490
August 16, 2004
Page 8

PATENT
Filed: April 12, 2001

43. (currently amended) The logic device of Claim [43]42, in combination with a communication device embodying the first and second computer communication interface components and a wireless IP transceiver.

44. (currently amended) The logic device of Claim [44]43, wherein the wireless transceiver operates in a frequency range of between two thousand three hundred million Hertz and two thousand three hundred ten million Hertz (2300mHz-2310mHz), inclusive.

45. (currently amended) The logic device of Claim [44]43, wherein the second computer communication interface component includes at least one USB connector, and the USB connector is connected to the transceiver with a cord.

46. (currently amended) The logic device of Claim [46]45, wherein the USB connector is a first USB connector, and the communication device includes a second USB connector attached to the cord and detachably engageable with a housing supporting the transceiver.

47. (currently amended) The logic device of Claim [47]46, further comprising at least one light emitting diode (LED) mounted on the housing and operable at least to indicate whether the transceiver is communicating with a base station.

48. (currently amended) The logic device of Claim [48]47, further comprising at least one audio speaker on the housing.

49. (currently amended) The logic device of Claim [49]48, further comprising at least one battery included in the housing.

50. (currently amended) The logic device of Claim [50]49, further comprising at least one audio or visual indication of a low voltage condition of the battery.

1168-19.AMD

CASE NO.: 50P4581
Serial No.: 09/833,490
August 16, 2004
Page 9

PATENT
Filed: April 12, 2001

51. (original) The device of Claim 1, wherein the wireless transceiver operates in a frequency range of between nine kiloHertz and fifty gigaHertz (9kHz-50GHz), inclusive.

52. (original) The device of Claim 16, wherein the wireless transceiver operates in a frequency range of between nine kiloHertz and fifty gigaHertz (9kHz-50GHz), inclusive.

53. (original) The device of Claim 27, wherein the wireless transceiver operates in a frequency range of between nine kiloHertz and fifty gigaHertz (9kHz-50GHz), inclusive.

54. (currently amended) The logic device of Claim [44]43, wherein the wireless transceiver operates in a frequency range of between nine kiloHertz and fifty gigaHertz (9kHz-50GHz), inclusive.

55. (currently amended) The device of Claim 14 A wireless communication device for providing at least two communication interfaces, comprising:

at least one antenna;

at least a first computer communication interface component electrically associated with the antenna, the first computer communication interface component defining a first interface format and being a memory device; and

at least a second computer communication interface component electrically associated with the antenna, the second computer communication interface component defining a second interface format, wherein the device can be used to establish wireless communication between at least one user terminal and at least one base station using one of the interface formats, wherein the first interface format is a flash memory format and the second interface format is selected from the group of formats comprising: universal serial bus (USB) format, Bluetooth wireless format, and ILink format, wherein the memory card has at least one chamfered surface.

1168-19.AMD

CASE NO.: 50P4581
Serial No.: 09/833,490
August 16, 2004
Page 10

PATENT
Filed: April 12, 2001

56. (currently amended) ~~The device of Claim 14~~ A wireless communication device for providing at least two communication interfaces, comprising:

at least one antenna;

at least a first computer communication interface component electrically associated with the antenna, the first computer communication interface component defining a first interface format and being a memory device; and

at least a second computer communication interface component electrically associated with the antenna, the second computer communication interface component defining a second interface format, wherein the device can be used to establish wireless communication between at least one user terminal and at least one base station using one of the interface formats, wherein the first interface format is a flash memory format and the second interface format is selected from the group of formats comprising: universal serial bus (USB) format, Bluetooth wireless format, and ILink format, wherein the memory card has a length of fifty millimeters (50mm) and a width of twenty one and a half millimeters (21.5mm).

57. (currently amended) ~~The device of Claim 14~~ A wireless communication device for providing at least two communication interfaces, comprising:

at least one antenna;

at least a first computer communication interface component electrically associated with the antenna, the first computer communication interface component defining a first interface format and being a memory device; and

1108-19.AMD

CASE NO.: 50P4581
Serial No.: 09/833,490
August 16, 2004
Page 11

PATENT
Filed: April 12, 2001

at least a second computer communication interface component electrically associated with the antenna, the second computer communication interface component defining a second interface format, wherein the device can be used to establish wireless communication between at least one user terminal and at least one base station using one of the interface formats, wherein the first interface format is a flash memory format and the second interface format is selected from the group of formats comprising: universal serial bus (USB) format, Bluetooth wireless format, and ILink format, wherein the flash memory card has ten connectors.

58. (currently amended) The device of Claim 27, A device for effecting wireless communication between a user terminal and at least one base station, comprising:

wireless transmitting means;

first communication interface and flash memory means engageable with a user terminal for communicating IP data from the user terminal to the base station using the wireless transmitting means; and

second communication interface means engageable with a user terminal for communicating IP data from the user terminal to the base station using the wireless transmitting means, the first and second communication interface means being contained on a housing separate from the user terminal, wherein the first communication interface and flash memory means is at least one flash memory card, the second communication interface means is at least one universal serial bus (USB) connector, and the wireless transmitting means is at least one wireless Internet packet (IP) transceiver, wherein the memory card has a chamfered surface.

1168-19.AMD

CASE NO.: 50P4581
Serial No.: 09/833,490
August 16, 2004
Page 12

PATENT
Filed: April 12, 2001

59. (currently amended) ~~The device of Claim 27,~~ A device for effecting wireless communication between a user terminal and at least one base station, comprising:

wireless transmitting means;

first communication interface and flash memory means engageable with a user terminal for communicating IP data from the user terminal to the base station using the wireless transmitting means; and

second communication interface means engageable with a user terminal for communicating IP data from the user terminal to the base station using the wireless transmitting means, the first and second communication interface means being contained on a housing separate from the user terminal, wherein the first communication interface and flash memory means is at least one flash memory card, the second communication interface means is at least one universal serial bus (USB) connector, and the wireless transmitting means is at least one wireless Internet packet (IP) transceiver, wherein the memory card has a length of fifty millimeters (50mm) and a width of twenty one and a half millimeters (21.5mm).

60. (currently amended) ~~The device of Claim 27,~~ A device for effecting wireless communication between a user terminal and at least one base station, comprising:

wireless transmitting means;

first communication interface and flash memory means engageable with a user terminal for communicating IP data from the user terminal to the base station using the wireless transmitting means; and

1168-19.AMD

CASE NO.: 50P4581
Serial No.: 09/833,490
August 16, 2004
Page 13

PATENT
Filed: April 12, 2001

second communication interface means engageable with a user terminal for communicating IP data from the user terminal to the base station using the wireless transmitting means, the first and second communication interface means being contained on a housing separate from the user terminal, wherein the first communication interface and flash memory means is at least one flash memory card, the second communication interface means is at least one universal serial bus (USB) connector, and the wireless transmitting means is at least one wireless Internet packet (IP) transceiver., wherein the flash memory card has at least ten connectors.

1168-19.AMD